

VISUAL FAULT LOCATOR

光纖斷點檢測器

MODEL NO. : VFL-250



Main feature:

- ◆ Visual Fault Locator is used for locating broken point in fibers .
- ◆ Visual Fault Locator is equipped with a 650-nm visible laser diode , can be operated in continuous or pulse modes for clear noticeable results .
- ◆ One green LED indicator shows the operating mode .
- ◆ Power switch on the end for battery on / off .
- ◆ Push button operate CW / Mod. (2.5 Hz frequency) / pause .
- ◆ Clip pocket-size pen design .
- ◆ Protective cap for extra protection .

Specification:

Central Wavelength	650 +/- 10 nm
Output Power	1mW into Single-mode fiber
Spectral Width	< 10 nm
Transmission	CW or 2.5 Hz pulse
Batteries	2 x AAA Alkaline batteries
Operating Temp.	0 - 50 °C
Detecion Distance	< 6 Km
Dimension / Weigth	13.5 mm X 170 mm / 88 g
Light Source	Class 3A laser diode
Option	Adapter Type , (AC Adapter , DC 3V)

Order:

PART #	-	Type	
VFL-250			(For Batteries Type)
VFL-250		A	(For Adapter Type)

FiberSource Trading Incorporation

fibersource@fibersource.com.tw